NSN 5930-01-352-7822

Code Indicating Wheel Switch - Page 1 of 2



7822

View Online at https://aerobasegroup.com/nsn/5930-01-352-7
Hazardous Locations/environmental Protection:
Explosion proof and salt spray resistant
Overall Length:
3.760 inches
Overall Height:
1.875 inches
Overall Width:
1.150 inches
Unthreaded Mounting Hole Diameter:
0.100 inches single mounting facility
Individual Section Quantity:
6
Longest Vertical Distance Between Mounting Centers:
0.900 inches single mounting facility
Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

12 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 each section

Contact Arrangement Truth Table:

Decimal, 1 pole - 12 positions each section

Color:

Black each bodyblack each indicator backgroundwhite each indicator marking

Precious Material And Location:

Printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

NSN 5930-01-352-7822

Code Indicating Wheel Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A052b0