

View Online at <https://aerobasegroup.com/nsn/5930-01-352-8514>

Thread Class:

3b single pressure connectiona2b all threaded hole

Inside Diameter:

0.438 inches single connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.050 inches

Overall Height:

1.380 inches

Overall Width:

2.030 inches

Body Length:

2.000 inches

Longest Horizontal Distance Between Mounting Centers:

0.750 inches

Longest Vertical Distance Between Mounting Centers:

1.750 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch absolute

Thread Size:

0.438 inches single pressure connection0.138 inches all threaded hole

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage and 4.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

16.00 actuation point pounds per square inch absolute and 17.50 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel nut with compression sleeve, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unjf single pressure connectionunc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0