

View Online at <https://aerobasegroup.com/nsn/5930-01-352-9880>

Unthreaded Mounting Hole Diameter:

0.189 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes inductive load highest ac voltage rating at sea level10.0 amperes inductive load lowest ac voltage rating at sea level10.0 amperes inductive load highest dc voltage rating at sea level10.0 amperes inductive load lowest dc voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0