

View Online at <https://aerobasegroup.com/nsn/5930-01-352-9880>

**Unthreaded Mounting Hole Diameter:**

0.189 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes inductive load highest ac voltage rating at sea level10.0 amperes inductive load lowest ac voltage rating at sea level10.0 amperes inductive load highest dc voltage rating at sea level10.0 amperes inductive load lowest dc voltage rating at sea level

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0