

View Online at <https://aerobasegroup.com/nsn/5930-01-353-1425>

Thread Length:

0.781 inches single pressure connection

Overall Length:

3.469 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

1.370 inches

Overall Width:

2.070 inches

Body Length:

2.063 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

600.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

0.75 amperes resistive load first voltage5.8 amperes resistive load second voltage2.9 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+500.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

445.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

24.0 ac at sea level first voltage120.0 ac at sea level second voltage240.0 ac at sea level third voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A048b0