

View Online at <https://aerobasegroup.com/nsn/5930-01-353-1425>

**Thread Length:**

0.781 inches single pressure connection

**Overall Length:**

3.469 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Height:**

1.370 inches

**Overall Width:**

2.070 inches

**Body Length:**

2.063 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Input port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

600.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

0.75 amperes resistive load first voltage5.8 amperes resistive load second voltage2.9 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+100.00/+500.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Stimulus Rating:**

445.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

24.0 ac at sea level first voltage120.0 ac at sea level second voltage240.0 ac at sea level third voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Ptf-sae short single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0