# NSN 5930-01-353-1430

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-353-1430

# **Thread Class:**

2b single mounting facility

# **Overall Length:**

5.813 inches

# **Overall Height:**

2.812 inches

# **Overall Width:**

2.812 inches

# Individual Section Quantity:

#### 8

# Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

# Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

# Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 each section periphery

## **Throw Quantity:**

7 each section periphery

## Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

# **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

## **Thread Size:**

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

240.0 ac at sea level125.0 dc at sea level

## Mounting Facility Pattern:

Four position rectangular single mounting facility

## Switch Actuator Indexing Position Quantity:

8 single actuator

## **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Breaks before makes each section periphery

# Switch Actuator Positioning Increment:

45.0 degrees single actuator

## **Contact Load Current Rating:**

5.0 amperes inductive load ac at sea level2.0 amperes inductive load dc at sea level

# NSN 5930-01-353-1430

Rotary Switch - Page 2 of 2

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

