NSN 5930-01-353-5450

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-353-5450

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Height:

2.875 inches

Overall Width:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 ac at sea level250.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Contact Load Current Rating:

1.0 amperes inductive load ac at sea level200.0 milliamperes inductive load dc at sea level

Special Features:

Legend plate reads off, normal

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-353-5450 Rotary Switch - Page 2 of 2

Fiig: A052b0

