NSN 5930-01-353-5450

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-353-5450
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Shock proof
Overall Height:
2.875 inches
Overall Width:
2.500 inches
Longest Horizontal Distance Between Mounting Centers:
1.062 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.062 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Threaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.164 inches single mounting facility
Contact Voltage Rating In Volts:
440.0 ac at sea level250.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Contact Load Current Rating:
1.0 amperes inductive load ac at sea level200.0 milliamperes inductive load dc at sea level
Special Features:
Legend plate reads off, normal
Style Designator:
In-line, cam actuated
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-353-5450 Rotary Switch - Page 2 of 2



Fiig:

A052b0