# NSN 5930-01-353-5459

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-353-5459

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.050 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Case Material:
Metal
Actuator Length:
0.640 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.640 inches
Actuator Color:
Red single actuator
Actuator Inscription:
Fire/push single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
End Application:
F-15 aircraft
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Four-way split lens
Nonpile-up Contact Arrangement:
Oracle devide the second both modification and state of the second

2 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-353-5459

Push Switch - Page 2 of 2



Criticality Code Justification	ion:
--------------------------------	------

Feat

### **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

### **Special Features:**

Weapon system essential

**Precious Material And Location:** 

Contact surfaces silver

### **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0