## NSN 5930-01-354-4091

Push Switch - Page 1 of 2

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-354-4091

Hazardous Locations/environmental Protection:
Moisture resistant and shock resistant and vibration resistant
Overall Length:
2.750 inches
Overall Height:
1.000 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.680 inches
Actuator Style:
Rectangular
Actuator Height:
0.250 inches
Actuator Width:
0.430 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Pwr single actuator
Maximum Voltage Rating In Volts:
220.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.500 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-354-4091

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac and 3.000 amperes resistive dc and 1.500 amperes inductive dc

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0