

View Online at <https://aerobasegroup.com/nsn/5930-01-354-4731>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.855 inches

Overall Height:

1.375 inches

Overall Width:

0.510 inches

Bushing Length:

0.352 inches

Body Length:

0.855 inches

Body Width:

0.510 inches

Body Height:

0.475 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.112 inches and 0.118 inches

Actuator Height:

Between 0.400 inches and 0.420 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac and 5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

Precious Material And Location:

Contact surfaces gold

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Specification Data:

81349-mil-s-83731/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0