NSN 5930-01-354-6682

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-354-6682

Thread Class: A2a single threaded stud **Thread Length:** 0.187 inches single threaded stud **Overall Height:** 0.867 inches **Body Height:** 0.437 inches **Overall Diameter:** Between 0.540 inches and 0.640 inches **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit **Mounting Method:** Threaded stud **Features Provided:** Hermetically sealed case Thready Qty Per Inch (tpi): 32 single threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.138 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load first voltage and 2.5 amperes inductive load first voltage and 1.0 amperes lamp load first voltage2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 210.00 actuation point degrees fahrenheit and 240.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 115.0 ac at sea level first voltage28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Disc

NSN 5930-01-354-6682

Thermostatic Switch - Page 2 of 2



Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single threaded stud

Specification Data:

81349-mil-s-24236/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0