

View Online at <https://aerobasegroup.com/nsn/5930-01-354-6684>

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant

Overall Length:

7.000 inches

Overall Height:

2.875 inches

Overall Width:

3.500 inches

Body Length:

5.875 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Capillary Tube Length:

5.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.375 inches

Longest Vertical Distance Between Mounting Centers:

6.219 inches

End Application:

3k gph rowpu.

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Terminal Type:

Wire lead

Contact Load Current Rating:

16.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+40.00/+100.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob with scale

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Special Features:

Weapon system essential

Frequency In Hertz:

50.0 single voltage and 60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0