

View Online at <https://aerobasegroup.com/nsn/5930-01-354-7262>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

Between 0.833 inches and 0.855 inches

Overall Height:

Between 1.444 inches and 1.580 inches

Overall Width:

Between 0.490 inches and 0.510 inches

Bushing Length:

Between 0.284 inches and 0.310 inches

Body Length:

Between 0.833 inches and 0.855 inches

Body Width:

Between 0.490 inches and 0.510 inches

Body Height:

Between 0.455 inches and 0.495 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.105 inches and 0.125 inches

Actuator Height:

Between 0.400 inches and 0.420 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 5.000 amperes resistive dc

Precious Material And Location:

Contact and terminals silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 wire wrap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0