

View Online at <https://aerobasegroup.com/nsn/5930-01-354-7262>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.833 inches and 0.855 inches

**Overall Height:**

Between 1.444 inches and 1.580 inches

**Overall Width:**

Between 0.490 inches and 0.510 inches

**Bushing Length:**

Between 0.284 inches and 0.310 inches

**Body Length:**

Between 0.833 inches and 0.855 inches

**Body Width:**

Between 0.490 inches and 0.510 inches

**Body Height:**

Between 0.455 inches and 0.495 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.105 inches and 0.125 inches

**Actuator Height:**

Between 0.400 inches and 0.420 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac and 5.000 amperes resistive dc

**Precious Material And Location:**

Contact and terminals silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 wire wrap

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0