

View Online at <https://aerobasegroup.com/nsn/5930-01-354-7765>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.284 inches and 0.310 inches

Body Length:

Between 0.833 inches and 0.855 inches

Body Width:

Between 0.490 inches and 0.510 inches

Body Height:

Between 0.520 inches and 0.590 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.105 inches and 0.125 inches

Actuator Height:

Between 0.400 inches and 0.420 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

12 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0