NSN 5930-01-355-1548

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-355-1548

| Body Style: | | | |
|--------------------------|---------------|--|--|
| Panel mounted | | | |
| Overall Length: | | | |
| 2.710 inches | | | |
| Overall Height: | | | |
| 0.750 inches | | | |
| Overall Width: | | | |
| 0.750 inches | | | |
| Body Length: | | | |
| 2.620 inches | | | |
| Body Width: | | | |
| 0.750 inches | | | |
| Body Height: | | | |
| 0.750 inches | | | |
| Case Material: | | | |
| Metal | | | |
| Actuator Length: | | | |
| 0.620 inches | | | |
| Actuator Style: | | | |
| Rectangular | | | |
| Actuator Height: | | | |
| 0.090 inches | | | |
| Actuator Width: | | | |
| 0.620 inches | | | |
| Actuator Color: | | | |
| Black single actuator | | | |
| Illuminated Actuator (| olor: | | |
| Black single actuator | | | |
| Actuator Inscription: | | | |
| Casi static input single | actuator | | |
| Maximum Voltage Rat | ing In Volts: | | |
| 28.0 dc | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Mounting Method: | | | |
| Panel | | | |
| Features Provided: | | | |
| Full display lens | | | |
| Nonpile-up Contact A | rangement: | | |

Contact Load Current Rating At Maximum Rated Voltage:

3 pole, double throw, both positions maintained single switch unit

1.000 amperes resistive dc and 1.000 amperes inductive dc and 500.0 milliamperes lamp dc

NSN 5930-01-355-1548

Push Switch - Page 2 of 2



| Special | Features: |
|----------------|-----------|
|----------------|-----------|

Legend illuminates amber

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

9 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0