## NSN 5930-01-355-2466

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-355-2466

Body Style: Panel mounted Body Length: 2.620 inches Body Width: 0.750 inches Body Height: 0.750 inches Actuator Length: 0.620 inches Actuator Style: Rectangular Actuator Height: 0.090 inches Actuator Width: 0.620 inches
Body Length:  2.620 inches  Body Width:  0.750 inches  Body Height:  0.750 inches  Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  0.090 inches  Actuator Width:
2.620 inches  Body Width: 0.750 inches  Body Height: 0.750 inches  Actuator Length: 0.620 inches  Actuator Style:  Rectangular  Actuator Height: 0.090 inches  Actuator Width:
Body Width:  0.750 inches  Body Height:  0.750 inches  Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  0.090 inches  Actuator Width:
0.750 inches  Body Height: 0.750 inches  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: 0.090 inches  Actuator Width:
Body Height:  0.750 inches  Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  0.090 inches  Actuator Width:
0.750 inches  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: 0.090 inches  Actuator Width:
Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  0.090 inches  Actuator Width:
0.620 inches  Actuator Style: Rectangular  Actuator Height: 0.090 inches  Actuator Width:
Actuator Style: Rectangular Actuator Height: 0.090 inches Actuator Width:
Rectangular  Actuator Height: 0.090 inches  Actuator Width:
Actuator Height: 0.090 inches Actuator Width:
0.090 inches  Actuator Width:
Actuator Width:
0.000 inches
U.620 Inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Diff/output/0.04/in/in/y-axis single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
28.000 amperes resistive dc and 500.0 milliamperes inductive dc
Special Features:
Amber illuminated legend
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
9 turret and 5 tab, solder lug
Shelf Life:

N/a

## NSN 5930-01-355-2466

Push Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0