## NSN 5930-01-355-7114

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-01-355-7114
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
6.813 inches
Overall Height:
4.375 inches
Overall Width:
3.688 inches
Individual Section Quantity:
11
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
1.609 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Thready Qty Per Inch (tpi):
20 single mounting facility
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
500.0 ac at sea level120.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed-adjustable stops single actuator
Contact Load Current Rating:
30.0 amperes inductive load ac at sea level and 30.0 amperes resistive load ac at sea level25.0 amperes inductive load dc at sea level an
30.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:

N/a

Shelf Life:

Unc single mounting facility

## **NSN 5930-01-355-7114**Rotary Switch - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

Demilitarization:

No

Fiig:

A052b0