## NSN 5930-01-355-7116



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-355-7116 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Bushing Length:** Between 0.115 inches and 0.135 inches **Body Length:** Between 0.235 inches and 0.265 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.105 inches and 0.115 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac **End Application:** 5895-01-340-3279 base station, communication terminal Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.164 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 500.0 milliamperes resistive ac **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5930-01-355-7116

Push Switch - Page 2 of 2



Fiig:

A053a0