## NSN 5930-01-356-4202

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-4202

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Shock resistant and vibration resistant

**Overall Length:** 

4.571 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.437 inches single actuator

**Overall Diameter:** 

1.170 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

8

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front1 each section front

**Throw Quantity:** 

7 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

7 single actuator

**Shaft Type:** 

Round, flatted single actuator

# NSN 5930-01-356-4202

Rotary Switch - Page 2 of 2



Terminal Type	Tern	ninal	Type
---------------	------	-------	------

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks 1st section rearmakes before breaks 2nd section rearmakes before breaks 3rd section rearmakes before breaks 4th section rearbreaks before makes 5th section rearbreaks before makes 6th section rearmakes before breaks 7th section rearmakes before breaks 8th section rear

#### **Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

#### **Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level100.0 milliamperes inductive load dc at sea level and 250.0 milliamperes resistive load dc at sea level

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material:** 

Gold

**Style Designator:** 

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A052b0