

View Online at <https://aerobasegroup.com/nsn/5930-01-356-4204>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

2.267 inches

Overall Height:

0.855 inches

Overall Width:

1.200 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.343 inches single actuator

Individual Section Quantity:

4

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

6625-01-260-9228 analyzer, distortion

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

12 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section periphery

Contact Load Current Rating:

250.0 milliamperes resistive load ac at sea level

Style Designator:

Wafer, printed board, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0