NSN 5930-01-356-4221

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-4221

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
2.960 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
An/srn-2 (v) navigation radio set; deep submergence systems programs (dssp)
Mounting Surface To Terminal End Distance:
2.660 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel and terminal
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac and 2.500 amperes inductive ac and 5.000 amperes resistive dc and 5.000 amperes inductive dc
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

11 pin

Specification Data:

81349-mil-s-22885/80 government specification

NSN 5930-01-356-4221

Push Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0