## NSN 5930-01-356-4225

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-4225

view Offilite at https://defobasegroup.com/hsi//0900-01-000-4220
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
2.360 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.450 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Safe parking on single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes

Contacts silver

inductive dc and 2.500 amperes lamp dc

**Precious Material And Location:** 

## NSN 5930-01-356-4225

Push Switch - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0