# NSN 5930-01-356-4225

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-4225

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Driptight and dustproof

#### **Overall Length:**

2.360 inches

#### **Overall Height:**

0.960 inches

#### **Overall Width:**

0.960 inches

#### **Body Width:**

0.750 inches

#### Body Height:

0.750 inches

#### Actuator Length:

#### 0.620 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.450 inches

### Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Black single actuator

#### **Actuator Inscription:**

Safe parking on single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

Between 1.720 inches and 1.880 inches

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes

inductive dc and 2.500 amperes lamp dc

#### **Precious Material And Location:**

Contacts silver

# NSN 5930-01-356-4225

Push Switch - Page 2 of 2



## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0