NSN 5930-01-356-5228

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-5228

| Body Style: |
|--|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof and driptight |
| Body Length: |
| 1.910 inches |
| Body Width: |
| 0.960 inches |
| Body Height: |
| 0.960 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.510 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.275 inches |
| Actuator Width: |
| 0.510 inches |
| Actuator Inscription: |
| Runway amid/on single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Printed circuit |
| Features Provided: |
| Horizontal split lens |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 6 tab, solder lug and 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-01-356-5228

Push Switch - Page 2 of 2



Fiig:

A053a0