

View Online at <https://aerobasegroup.com/nsn/5930-01-356-5770>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.100 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.000 inches

Mounting Method:

Line

Contact Action Stimulus:

Increase

Proof Pressure:

240.00 pounds per square inch gage

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

360.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 milliamperes resistive load single voltage and 200.0 milliamperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point pounds per square inch and 10.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Grooved, unthreaded external single connection

Media For Which Designed:

Gas or liquid

Nuclear Hardness Critical Feature:

Hardened

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0