## NSN 5930-01-356-5784

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-5784

Body Style:							
Panel mounted							
Hazardous Locations/environmental Protection:							
Dustproof							
Overall Length:							
2.320 inches							
Overall Height:							
0.750 inches							
Overall Width:							
0.750 inches							
Body Width:							
0.750 inches							
Body Height:							
0.750 inches							
Case Material:							
Metal							
Actuator Length:							
0.620 inches							
Actuator Style:							
Rectangular							
Actuator Height:							
0.150 inches							
Actuator Width:							
0.620 inches							
Actuator Inscription:							
1w1 e call rel single actuator							
Maximum Voltage Rating In Volts:							
28.0 dc							
Mounting Surface To Terminal End Distance:							
Between 1.820 inches and 1.980 inches							
Inclosure Type:							
Fully enclosed							
Mounting Method:							
Panel							
Features Provided:							
Full display lens							
Nonpile-up Contact Arrangement:							
4 pole, double throw, one position momentary single switch unit							
Contact Load Current Rating At Maximum Rated Voltage:							
7.000 amperes resistive dc and 4.000 amperes inductive ac							

**Precious Material And Location:** 

C0ntacts silver and c0ntact and terminal surfaces gold

## NSN 5930-01-356-5784

Push Switch - Page 2 of 2



			_	_			
 ทว	h	_	-	11	$\Delta$	$\sim$	de

Unable to decode and unable to decode

## **Terminal Type And Quantity:**

12 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0