

View Online at <https://aerobasegroup.com/nsn/5930-01-356-6506>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.500 inches

Overall Height:

1.155 inches

Overall Width:

0.400 inches

Bushing Length:

0.312 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.410 inches

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

0.650 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

6625-01-286-3572 voltmeter; spruance class dd (963); nimitz class cvn; los angeles class ssn (688); supply class aoe; ticonderoga class cg (47); oliver perry class ffg; arleigh burke class ddg; seawolf class ssn

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 5.000 amperes resistive dc

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0