## NSN 5930-01-356-6512

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-6512

Body Style: Panel mounted  Hazardous Locations/environmental Protection:  Dustracef
Hazardous Locations/environmental Protection:
Dustract
Dustproof
Overall Length:
2.320 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
Between 1.820 inches and 1.980 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc

## **Precious Material And Location:**

Contacts silver and terminal and contact surfaces gold

## **Unable To Decode:**

Unable to decode and unable to decode

## NSN 5930-01-356-6512

Push Switch - Page 2 of 2



Terminal Type A	and Quantity	<b>/:</b>
-----------------	--------------	-----------

12 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0