

View Online at <https://aerobasegroup.com/nsn/5930-01-356-8094>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.100 inches

Overall Height:

2.310 inches

Overall Width:

0.670 inches

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.670 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Specification Data:

81349-mil-s-8805/98 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0