

View Online at <https://aerobasegroup.com/nsn/5930-01-356-8445>

**Hazardous Locations/environmental Protection:**

Vibration proof

**Overall Length:**

3.520 inches

**Overall Height:**

1.740 inches

**Overall Width:**

2.120 inches

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

27192

**Knob Manufacturer Part Number:**

53-1160

**Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

750.0 milliamperes inductive load highest ac voltage rating at sea level3.0 amperes inductive load lowest ac voltage rating at sea level0.4 amperes inductive load highest dc voltage rating at sea level1.1 amperes inductive load lowest dc voltage rating at sea level

**Special Features:**

Legend plate reads: run stop

**Style Designator:**

Rectangular panel mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0