## NSN 5930-01-356-8451

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-356-8451

| view Offiline at https://derobasegroup.com/nsi//0300-01-030-0401              |
|---|
| Overall Length:   |
| 6.180 inches  |
| Overall Height:   |
| 2.520 inches  |
| Overall Width:  |
| 2.520 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.180 inches single mounting facility   |
| Individual Section Quantity:  |
| 4   |
| Knob Manufacturer Code:   |
| 10983   |
| Knob Manufacturer Part Number:  |
| G071  |
| Longest Horizontal Distance Between Mounting Centers:                         |
| 1.890 inches single mounting facility   |
| Longest Vertical Distance Between Mounting Centers:                           |
| 1.890 inches single mounting facility   |
| Switch Contact Basic Design:  |
| Nonpile-up nonsymmetrical   |
| Mounting Method:  |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Features Provided:  |
| Actuator knob and legend plate  |
| Contact Voltage Rating In Volts:  |
| 600.0 ac at sea level   |
| Mounting Facility Pattern:  |
| Four position rectangular single mounting facility                            |
| Switch Actuator Indexing Position Quantity:                                   |
| 2 single actuator   |
| Terminal Type:  |
| Screw   |
| Switch Actuator Positioning Increment:  |
| 60.0 degrees single actuator  |
| Switch Actuator Stop Device Type:   |
| Fixed-adjustable stops single actuator  |
| Contact Load Current Rating:  |
| 25.0 amperes resistive load ac at sea level                                   |
| Special Features:   |
| Legend plate reads 1, 2   |
| Precious Material And Location:   |

Contact surfaces silver

## NSN 5930-01-356-8451

Rotary Switch - Page 2 of 2



| P | reci | nus | Materia | ŀ |
|---|------|-----|---------|---|
|   |      |     |         |   |

Silver

**Style Designator:** 

In-line, cam actuated

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0