

View Online at <https://aerobasegroup.com/nsn/5930-01-356-9279>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.200 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.190 inches

Actuator Roller Diameter:

0.480 inches

Housing Height:

0.630 inches

Housing Length:

1.740 inches

Housing Width:

1.580 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

0.980 inches

Maximum Voltage Rating In Volts:

240.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

60.0 ounces

Switch Actuating Force:

60.0 ounces

Actuator Movement:

Between 0.071 pretravel inches and 0.118 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 1.200 amperes inductive ac and 3.000 amperes resistive dc and 3.000 amperes inductive dc

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0