

View Online at <https://aerobasegroup.com/nsn/5930-01-356-9279>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Unthreaded Mounting Hole Diameter:**

0.200 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.190 inches

**Actuator Roller Diameter:**

0.480 inches

**Housing Height:**

0.630 inches

**Housing Length:**

1.740 inches

**Housing Width:**

1.580 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

0.980 inches

**Maximum Voltage Rating In Volts:**

240.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

60.0 ounces

**Switch Actuating Force:**

60.0 ounces

**Actuator Movement:**

Between 0.071 pretravel inches and 0.118 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 1.200 amperes inductive ac and 3.000 amperes resistive dc and 3.000 amperes inductive dc

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0