NSN 5930-01-357-3306

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-357-3306

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.360 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
1.910 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
Natural single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
2y3 jf, capt/3r2 capt single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
4 pole double throw one position memortary single switch unit

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-357-3306

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

Precious Material And Location:

Contacts silver and contact and terminal surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

6 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0