NSN 5930-01-357-4204

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-357-4204

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Dustproof and driptight
Body Width:
0.960 inches
Body Height:
0.960 inches
Case Material:
Metal
Actuator Length:
0.510 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.510 inches
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
1.910 inches
Inclosure Type:
Fully enclosed
Fully enclosed Mounting Method:
Mounting Method:
Mounting Method: Panel
Mounting Method: Panel Features Provided:
Mounting Method: Panel Features Provided: Horizontal split lens
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage:
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity:
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret Shelf Life:
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret Shelf Life: N/a
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret Shelf Life: N/a
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret Shelf Life: N/a Unit Of Measure:
Mounting Method: Panel Features Provided: Horizontal split lens Contact Load Current Rating At Maximum Rated Voltage: 0.024 amperes resistive dc Terminal Type And Quantity: 6 tab, solder lug and 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: