

View Online at <https://aerobasegroup.com/nsn/5930-01-357-5550>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Dustproof and driptight

Overall Length:

2.360 inches

Overall Height:

0.960 inches

Overall Width:

0.960 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.450 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Jf; flg; p&b; flg; p&b single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

1.910 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Horizontal split lens and actuator seal

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes inductive dc and 7.000 amperes resistive dc and 2.500 amperes lamp dc and 7.000 amperes inductive ac and 7.000 amperes resistive ac and 2.000 amperes lamp ac

Special Features:

Top half of actuator inscription yellow bottom half of actuator inscription green

Precious Material And Location:

Terminal and contact surfaces silver

Terminal Type And Quantity:

3 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0