

View Online at <https://aerobasegroup.com/nsn/5930-01-357-5550>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Dustproof and driptight

**Overall Length:**

2.360 inches

**Overall Height:**

0.960 inches

**Overall Width:**

0.960 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.450 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Black single actuator

**Actuator Inscription:**

Jf; flg; p&b; flg; p&b single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

1.910 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Horizontal split lens and actuator seal

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes inductive dc and 7.000 amperes resistive dc and 2.500 amperes lamp dc and 7.000 amperes inductive ac and 7.000 amperes resistive ac and 2.000 amperes lamp ac

**Special Features:**

Top half of actuator inscription yellow bottom half of actuator inscription green

**Precious Material And Location:**

Terminal and contact surfaces silver

**Terminal Type And Quantity:**

3 turret and 6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0