## NSN 5930-01-357-5552

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-357-5552

Body Style:								
Panel mounted								
Hazardous Locations/environmental Protection:								
Dustproof and driptight								
Body Width:								
0.960 inches								
Body Height:								
0.960 inches								
Actuator Length:								
0.620 inches								
Actuator Style:								
Rectangular								
Actuator Height:								
0.275 inches								
Actuator Width:								
0.620 inches								
Actuator Color:								
Natural single actuator								
Illuminated Actuator Color:								
Natural single actuator								
Maximum Voltage Rating In Volts:								
Maximum Voltage Rating In Volts:								
Maximum Voltage Rating In Volts: 28.0 dc								
28.0 dc								
28.0 dc  Mounting Surface To Terminal End Distance:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:								
28.0 dc  Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 7.000 amperes resistive dc								
Mounting Surface To Terminal End Distance: 2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 7.000 amperes resistive dc Precious Material And Location:								
Mounting Surface To Terminal End Distance:  2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 7.000 amperes resistive dc Precious Material And Location: Contacts silver and contact and terminal surfaces gold								
Mounting Surface To Terminal End Distance:  2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 7.000 amperes resistive dc Precious Material And Location: Contacts silver and contact and terminal surfaces gold Unable To Decode:								
Mounting Surface To Terminal End Distance:  2.360 inches Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided: Actuator seal and horizontal split lens Nonpile-up Contact Arrangement: 4 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 7.000 amperes resistive dc Precious Material And Location: Contacts silver and contact and terminal surfaces gold Unable To Decode: Unable to decode and unable to decode								

N/a

## NSN 5930-01-357-5552

Push Switch - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A053a0