

View Online at <https://aerobasegroup.com/nsn/5930-01-358-1312>

**Body Style:**

Panel mount

**Overall Length:**

1.136 inches

**Overall Height:**

1.845 inches

**Overall Width:**

Between 0.785 inches and 0.815 inches

**Body Length:**

1.136 inches

**Body Width:**

Between 0.785 inches and 0.815 inches

**Body Height:**

1.400 inches

**Actuator Length:**

0.990 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.275 inches

**Actuator Width:**

0.610 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**End Application:**

Simulator, countermeasures signals an/ulq-13

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes inductive ac and 2.000 amperes resistive dc

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

81349-mil-s-22885/93 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0