

View Online at <https://aerobasegroup.com/nsn/5930-01-358-1313>

Body Style:

Panel mount

Overall Length:

1.136 inches

Overall Height:

1.845 inches

Overall Width:

Between 0.785 inches and 0.815 inches

Body Length:

1.136 inches

Body Width:

Between 0.785 inches and 0.815 inches

Body Height:

1.400 inches

Actuator Length:

0.990 inches

Actuator Style:

Rectangular

Actuator Height:

0.275 inches

Actuator Width:

0.610 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

End Application:

Simulator, countermeasures signals an/ulq-13

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive ac and 2.000 amperes resistive ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-s-22885 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0