# NSN 5930-01-358-2470

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-358-2470

# Body Style:

Panel mounted

#### Hazardous Locations/environmental Protection:

Vibration resistant

### **Body Length:**

1.000 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### **Overall Diameter:**

0.750 inches

#### **Case Material:**

Metal

#### Actuator Length:

----

# 0.520 inches

Actuator Style:

Rectangular

# Actuator Height:

0.260 inches

# Actuator Width:

0.520 inches

#### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Black single actuator

#### **Actuator Inscription:**

Rf xmtr power single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

Surface anti-submarine warfare combat system an/sqq-8 (v)

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# **Features Provided:**

Rfi shielding

# Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

# NSN 5930-01-358-2470

Push Switch - Page 2 of 2

Special Features: When illuminated letters appear in red Precious Material And Location: Terminal surfaces and contacts gold Terminal Type And Quantity: 11 turret Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A053a0

