NSN 5930-01-358-2472

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-358-2472
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture resistant and shock resistant and dustproof
Body Width:
0.740 inches
Body Height:
0.740 inches
Case Material:
Metal
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
End Application:
Deep submergence systems program (dssp); an/srn-2 (v) navigation radio set
Mounting Surface To Terminal End Distance:
2.960 inches
nclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Criticality Code Justification:
=eat
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac
Special Features:
Weapon system essential
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 socket, integrated wire termination
Specification Data:
31349-mil-s-22885/80 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

A053a0

Fiig: