

View Online at <https://aerobasegroup.com/nsn/5930-01-358-2675>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

4.400 inches

Overall Height:

Between 1.470 inches and 1.530 inches

Overall Width:

Between 1.470 inches and 1.530 inches

Unthreaded Mounting Hole Diameter:

Between 0.208 inches and 0.214 inches

Distance Between Mounting Facility Centers:

Between 1.115 inches and 1.135 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 0.0 degrees celsius and 65.0 degrees celsius

Mounting Method:

Base and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

300.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

11.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

68.00 actuation point pounds per square inch gage and 23.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Special Features:

Connector receptacle with cable is 19.000 lg.

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0