## NSN 5930-01-358-3129

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-358-3129 **Thread Class:** 2a single mounting facility **Overall Length:** 6.465 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Distance Between Mounting Facility Centers:** 1.625 inches single mounting facility **Individual Section Quantity:** 10 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

600.0 highest ac voltage rating at sea level 120.0 lowest ac voltage rating at sea level

#### **Mounting Facility Pattern:**

Four position circular single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

8 single actuator

#### **Terminal Type:**

Screw

#### **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

#### **Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

#### **Contact Load Current Rating:**

4.0 amperes inductive load highest ac voltage rating at sea level 15.0 amperes inductive load lowest ac voltage rating at sea level

#### **Precious Material And Location:**

Contact and rotor blade surfaces silver

#### **Precious Material:**

Silver

### Style Designator:

Tap, circuit selector

# NSN 5930-01-358-3129

Rotary Switch - Page 2 of 2



	T	hr	ead	<b>Series</b>	Design	nator
--	---	----	-----	---------------	--------	-------

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0