NSN 5930-01-358-3129

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-358-3129 **Thread Class:** 2a single mounting facility **Overall Length:** 6.465 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Distance Between Mounting Facility Centers:** 1.625 inches single mounting facility **Individual Section Quantity:** 10 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level 120.0 lowest ac voltage rating at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

4.0 amperes inductive load highest ac voltage rating at sea level 15.0 amperes inductive load lowest ac voltage rating at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

NSN 5930-01-358-3129

Rotary Switch - Page 2 of 2



	T	hr	ead	Series	Design	nator
--	---	----	-----	---------------	--------	-------

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0