

View Online at <https://aerobasegroup.com/nsn/5930-01-358-8500>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

1.312 inches

Overall Height:

2.764 inches

Overall Width:

0.840 inches

Bushing Length:

0.470 inches

Body Length:

1.312 inches

Body Width:

0.840 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

1.220 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Aircraft, tomcat f-14a

Mounting Surface To Terminal End Distance:

Between 1.017 inches and 1.077 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 4.000 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.500 amperes lamp dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0