

View Online at <https://aerobasegroup.com/nsn/5930-01-358-8500>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

1.312 inches

**Overall Height:**

2.764 inches

**Overall Width:**

0.840 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.312 inches

**Body Width:**

0.840 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

1.220 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Aircraft, tomcat f-14a

**Mounting Surface To Terminal End Distance:**

Between 1.017 inches and 1.077 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Mounting hardware

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 4.000 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.500 amperes lamp dc

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0